NSN 3010-00-776-0686

Gearcase-motor - Page 1 of 2

Overall Height:



View Online at https://aerobasegroup.com/nsn/3010-00-776-0686

| 1.688 inches |
|---|
| Overall Length: |
| 4.418 inches |
| Overall Width: |
| 1.688 inches |
| Shaft Diameter: |
| 0.3130 inches single end |
| Current Type: |
| Ac input |
| Maximum Operating Altitude Rating: |
| 50000.0 feet |
| Shaft Rotation Direction: |
| Counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Explosion proof |
| Winding Type: |
| Synchronous split phase |
| Mounting Method: |
| Pad |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Geared Head Output Shaft Alignment Position: |
| Inline w/armature single end |
| Cooling Method: |
| Nonventilated |
| Current Rating Method: |
| Load |
| Torque Rating And Type: |
| 2.25 inch-pounds running and 2.25 inch-pounds stalled and 2.25 inch-pounds starting |
| Inclosure Specificationification: |
| Commercial |
| Features Provided: |
| Vertical mounting position and horizontal mounting position |
| Length Of Shaft From Housing: |
| 1.093 inches single end |
| Tempurature Rating: |
| -55.0 operating degrees celsius and 71.0 operating degrees celsius and 55.0 ambient degrees celsius |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.375 inches |

NSN 3010-00-776-0686

Gearcase-motor - Page 2 of 2



| Center To Center Distance Between Mounting Facilities Parallel To Height: |
|---|
| 1.375 inches |
| Current Rating In Amps: |
| 0.210 single output |
| Connection Type And Voltage Rating In Volts: |
| 117.0 line to neutral single input |
| Geared Head Output Shaft Speed Rating: |
| 56.250 single revolutions per minute single end |
| Angle Of Shaft To Mounting Base: |
| 90.0 degrees single end |
| Shaft End Characteristic: |
| A1 single style single end |
| Phase: |
| Single input |
| Frequency In Hertz: |
| 60.0 input |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |

No Fiig: A271a0