# NSN 3010-00-822-4853

Rigid Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-00-822-4853

#### Spline Minor Diameter:

1.5010 inches both ends

#### Spline Major Diameter:

1.6940 inches both ends

### **Overall Length:**

3.922 inches

#### **Spline Quantity:**

26 both ends

#### Thread Size Designator:

1/4-20

#### **Overall Diameter:**

3.250 inches

#### **End Application:**

Test stand, aircraft generator

#### Bore Shape:

Splined both ends

# Spline Pressure Angle In Deg:

30.000 both ends

#### Spline Length:

1.000 inches both ends

#### Spline Type:

Involute both ends

#### Securing Method:

Threaded hole

#### **Threaded Hole Quantity:**

2

#### Features Provided:

Integral key and bore counterbore

#### **Body Material:**

Steel

#### **Special Features:**

Counterbore diameter: both ends, 1.5005 in.; counterbore depth: both ends, 2.3125 in.; distance from center of bore to top of key: both ends, 1.000 in.; pitch diameter: both ends, 1.625 in.; furnished items; 1 collar, 2 screws; 1 keying facility provided both ends; keying facility width: both ends, 0.375 in.

#### Surface Treatment:

Cadmium

#### Style Designator:

Plain sleeve

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

# **NSN 3010-00-822-4853** Rigid Shaft Coupling - Page 2 of 2

Fiig: A522c0

