## NSN 3010-00-834-2412

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-834-2412

view Offilite at https://defobasegroup.com/hsh/sorto-oo-os-4-2-412
Body Style:
Flexible key insert type, partial bore
Overall Length:
0.813 inches
Bore Diameter:
0.2513 inches
Bore Length:
0.3130 inches
Bore Shape:
Straight
Features Provided:
Keyway
Special Features:
Fsc application data: test set, radio, except specially designed; surface treatment: chromium; body keying facility wd: 0.128" nom.; hole
thread size designator: (0.190") -32; threaded hole location: on hub portion of coupling between hub end and face spaced 90 deg. Apart;
threaded hole qty: 2; securing method: threaded hole; bore counterbore feature: not included; keying facility spacing in deg.: 180; keying
facility qty: 2; keying facility: included; o/a outside dimension: 0.750" nom.; hub od: 0.560" nom.; thread provision: unthreaded; distance
form center of bore to bottom of keyway: 0.341" nom.; keyway wd: 0.128" nom.; flange thickness: 0.438" nom.
Material:
Zinc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A521x0