

View Online at <https://aerobasegroup.com/nsn/3010-00-868-1119>

Body Style:

2 lugs

Spline Major Diameter:

Between 0.6867 inches and 0.6883 inches

Overall Length:

Between 3.667 inches and 3.672 inches

Outside Diameter:

4.000 inches

Spline Quantity:

10

Bore Shape:

Splined

Special Features:

Fsc application data: mount, howitzer, 155 mm, m80 /t167/; distance from bore counterbore to body keying facility bottom/top: 1.375" nom.; body keying facility dep/ht: 0.427" min., 0.432" max.; body keying facility wd: 0.5615" min., 0.5620" max.; bore counterbore feature: included; keying facility: not included; counterbore location: coupling end; spline lg.: 1.625" nom.; hub od: 1.500" nom.; thread provision: unthreaded; bore lg.: 3.198" min., 3.203" max.; flange thickness: 1.063" nom.; counterbore dep.: 1.578" nom.; counterbore dia.: 0.813" nom.; spline minor dia.: 0.5625" min., 0.5650" max.

Material:

Steel

Material Specification:

Qq-s-633, amend. 2, fs 1020, fs 1025 or fs 1030 federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A521x0