# NSN 3010-00-969-4917

Flexible Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-00-969-4917

Hole Diameter:

0.129 inches both ends

Spline Minor Diameter:

0.4520 inches both ends

# Spline Major Diameter:

0.5000 inches both ends

**Overall Length:** 

2.063 inches

### **Outside Diameter:**

1.438 inches

Keyway Width:

0.0634 inches both ends

#### Keyway Depth:

0.0400 inches both ends

#### Spline Quantity:

11 both ends

#### Thread Size Designator:

No. 10-32 /0.190 in./ both ends

#### Bore Diameter:

0.3130 inches second end

### Bore Length:

0.8130 inches second end

# Bore Shape:

Straight second end

#### Design Type:

Insert

#### Spline Length:

0.813 inches both ends

## **Keying Facility Quantity:**

1 both ends

#### Keying Facility Type:

Keyway both ends

### Securing Method:

Unthreaded hole first end

#### **Threaded Hole Quantity:**

1 both ends

# **Threaded Hole Location:**

Both ends: located 180 degrees from keyway

## **Unthreaded Hole Quantity:**

1 both ends

# **Unthreaded Hole Location:**

Both ends: located through hub portion of coupling

# NSN 3010-00-969-4917

Flexible Shaft Coupling - Page 2 of 2

**Features Provided:** 

Keyway

Insert Material:

Copper alloy

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A522b0

