NSN 3010-01-009-4257

Rigid Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-01-009-4257 **Hole Diameter:** Between 0.0930 inches and 0.0980 inches **Spline Minor Diameter:** 0.3500 inches both ends **Spline Major Diameter:** 0.3810 inches both ends **Overall Length:** 2.060 inches **Spline Quantity:** 20 both ends **Overall Diameter:** 0.562 inches **Bore Shape:** Splined both ends Spline Pressure Angle In Deg: 45.000 both ends Spline Length: 2.060 inches both ends Spline Type: Involute both ends **Securing Method:** Unthreaded hole **Unthreaded Hole Quantity: Features Provided:** Bore counterbore **Body Material:** Stainless steel **Special Features:** Pitch diameter: 0.359 in.; tubing is 0.562 in. diameter, 0.125 in. Wall thick; omit three serrations to minor diameter **Material Specification:** Ams 5738 assn standard 1st material response or mil-t-6845 military specification 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Style Designator:** Plain sleeve Shelf Life:

N/a

Unit Of Measure:

NSN 3010-01-009-4257

Rigid Shaft Coupling - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A522c0

Mil-std (military Standard):

Mil-t-6845 spec.