# NSN 3010-01-011-3843

Rigid Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-01-011-3843

### Hole Diameter:

Between 0.093 inches and 0.098 inches

Spline Minor Diameter:

0.350 inches both ends

Spline Major Diameter:

0.381 inches both ends

#### **Overall Length:**

Between 0.674 inches and 0.678 inches

#### Spline Quantity:

1 both ends

### **Overall Diameter:**

0.562 inches

#### Bore Shape:

Splined both ends

Spline Pressure Angle In Deg:

### 45.000 both ends

Spline Length:

0.676 inches both ends

#### Spline Type:

Involute both ends

### Securing Method:

Unthreaded hole

#### **Unthreaded Hole Quantity:**

2

#### **Body Material:**

Steel comp 303f

#### **Special Features:**

With 0.870 in. Diameter by 0.062 in. Thk flange located 0.188 in. From end opposite hole, omit three serrations to minor diameter of bore

#### **Material Specification:**

Ams 5738 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

#### Style Designator:

Plain sleeve

### Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

# NSN 3010-01-011-3843

Rigid Shaft Coupling - Page 2 of 2

**Fiig:** A522c0

Mil-std (military Standard):

Mil-f-14072 spec.

