## NSN 3010-01-024-8981

Rigid Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-01-024-8981 **Hole Diameter:** Between 0.0710 inches and 0.0780 inches **Spline Minor Diameter:** 0.3120 inches first end and 0.3160 inches first end **Spline Major Diameter:** 0.4000 inches first end and 0.4170 inches first end **Overall Length:** 0.900 inches **Spline Quantity:** 11 first end **Overall Diameter:** 0.625 inches **Bore Shape:** Splined first end Spline Pressure Angle In Deg: 30.000 first end Spline Length: 0.000 inches first end Spline Type: Involute first end **Securing Method:** Unthreaded hole **Unthreaded Hole Quantity: Body Material:** Steel comp 4130 **Special Features:** Pitch diameter: 0.344 in.; furnished items: 1 cotter pin **Material Specification:** Mil-s-6758 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Cva5-2, cage 80378 mfr ref single treatment response **Style Designator:** Plain sleeve Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 3010-01-024-8981

Rigid Shaft Coupling - Page 2 of 2



Fiig:

A522c0

Mil-std (military Standard):

Mil-s-6758 spec.