## NSN 3010-01-089-3966

Gearcase-motor - Page 1 of 2

Single input



View Online at https://aerobasegroup.com/nsn/3010-01-089-3966

| Overall Height: 6.188 inches Overall Length: 7.750 inches Overall Width: 5.625 inches Shaft Diameter: 0.3875 inches identical ends Current Type: Ac input Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage |  |  |  |  |
|--|--|--|--|--|
| Overall Length: 7.750 inches Overall Width: 5.625 inches Shaft Diameter: 0.3875 inches identical ends Current Type: Ac input Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage                              |  |  |  |  |
| 7.750 inches  Overall Width: 5.625 inches  Shaft Diameter: 0.3875 inches identical ends  Current Type: Ac input  Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends  Duty Cycle: Continuous Inclosure Feature: Totally enclosed  Winding Type: Induction-squirrel cage  |  |  |  |  |
| Overall Width: 5.625 inches Shaft Diameter: 0.3875 inches identical ends Current Type: Ac input Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage   |  |  |  |  |
| 5.625 inches  Shaft Diameter: 0.3875 inches identical ends  Current Type: Ac input  Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends  Duty Cycle: Continuous Inclosure Feature: Totally enclosed  Winding Type: Induction-squirrel cage   |  |  |  |  |
| Shaft Diameter:  0.3875 inches identical ends  Current Type: Ac input  Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends  Duty Cycle: Continuous Inclosure Feature: Totally enclosed  Winding Type: Induction-squirrel cage  |  |  |  |  |
| 0.3875 inches identical ends  Current Type: Ac input  Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends  Duty Cycle: Continuous Inclosure Feature: Totally enclosed  Winding Type: Induction-squirrel cage   |  |  |  |  |
| Current Type: Ac input Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage  |  |  |  |  |
| Ac input  Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends  Duty Cycle: Continuous Inclosure Feature: Totally enclosed  Winding Type: Induction-squirrel cage   |  |  |  |  |
| Shaft Rotation Direction: Clockwise identical ends or counterclockwise identical ends Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage   |  |  |  |  |
| Clockwise identical ends or counterclockwise identical ends  Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage  |  |  |  |  |
| Duty Cycle: Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage   |  |  |  |  |
| Continuous Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage   |  |  |  |  |
| Inclosure Feature: Totally enclosed Winding Type: Induction-squirrel cage  |  |  |  |  |
| Totally enclosed  Winding Type: Induction-squirrel cage  |  |  |  |  |
| Winding Type: Induction-squirrel cage  |  |  |  |  |
| Induction-squirrel cage  |  |  |  |  |
|  |  |  |  |  |
|  |  |  |  |  |
| Mounting Facility Type And Quantity:   |  |  |  |  |
| 4 unthreaded hole  |  |  |  |  |
| Geared Head Output Shaft Alignment Position:   |  |  |  |  |
| Inline w/armature identical ends   |  |  |  |  |
| Cooling Method:  |  |  |  |  |
| Nonventilated  |  |  |  |  |
| Speed Control Method And Device Type:  |  |  |  |  |
| Automatic mechanical   |  |  |  |  |
| Features Provided:   |  |  |  |  |
| Horizontal mounting position   |  |  |  |  |
| Length Of Shaft From Housing:  |  |  |  |  |
| 0.475 inches identical ends  |  |  |  |  |
| Shaft Center To Mounting Surface Distance:   |  |  |  |  |
| 3.344 inches identical ends  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  |  |  |  |  |
| 4.062 inches   |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:   |  |  |  |  |
| 4.875 inches   |  |  |  |  |
| Connection Type And Voltage Rating In Volts:   |  |  |  |  |
| 24.0 line to neutral single input  |  |  |  |  |
| Shaft End Characteristic:  |  |  |  |  |
| A15 single style identical ends  |  |  |  |  |
| Phase:   |  |  |  |  |

## NSN 3010-01-089-3966

Gearcase-motor - Page 2 of 2



|  | S | pecial | Features: | • |
|--|---|--------|-----------|---|
|--|---|--------|-----------|---|

**Dual potentiometers** 

## Frequency In Hertz:

50.0 input or 60.0 input

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A271a0