

View Online at <https://aerobasegroup.com/nsn/3010-01-168-0569>

Overall Height:

2.875 inches

Overall Length:

3.125 inches

Overall Width:

3.000 inches

Shaft Diameter:

0.3120 inches single end

Flatted Portion Length:

0.6250 inches single end

Current Type:

Ac input

Flat Depth:

0.0310 inches single end

Shaft Rotation Direction:

Clockwise single end

Duty Cycle:

Continuous

Inclosure Feature:

Open

Specific Use:

Drives the transport assembly

Winding Type:

Synchronous shaded pole

Mounting Method:

Pad

Mounting Facility Type And Quantity:

4 threaded hole

Geared Head Output Shaft Alignment Position:

Angled to armature/rotor axis single end

Cooling Method:

Ambient air

Bearing Type:

Sleeve

Features Provided:

Vertical mounting position

Cubic Measure:

0.016 cubic feet

Length Of Shaft From Housing:

0.750 inches single end

Shaft Center To Mounting Surface Distance:

0.750 inches first end

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.375 inches

Connection Type And Voltage Rating In Volts:

115.0 line to neutral single input

Geared Head Output Shaft Speed Rating:

1125.000 single revolutions per minute single end

Angle Of Shaft To Mounting Base:

9090.0 degrees first end

Shaft End Characteristic:

A5 single style single end

Product Name:

Gearcase motor 60h 115v processor xray film

Phase:

Single input

Special Features:

Three leads 12 in. Lg, terminated by 3 female 1/4 in. Lg quick disconnect term

Frequency In Hertz:

60.0 input

Reference Data And Literature:

Manufactures manuals on the peri-pro x-ray film processor

Terminal Type And Quantity:

3 connector, plug

Fsc Application Data:

Processor, x-ray film

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A271a0