NSN 3010-01-243-9057

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-01-243-9057

Body	C41.	
DUUV	OLV.	œ.

Multiple positioning holes, recessed face

Overall Length:

Between 2.720 inches and 2.780 inches

Bore Diameter:

Between 1.0800 inches and 1.1120 inches

Bore Length:

Between 1.2200 inches and 1.2800 inches

Bore Shape:

Straight

Special Features:

L.H. Thread; material: a/a; positioning facility bolt circle dia.: 2.240" min., 2.345" max.; positioning facility gty: 3; unthreaded hole location: on flange; unthreaded hole qty: 3; securing method: unthreaded hole; bore counterbore feature: included; keying facility: not included; counterbore location: hub end; o/a outside dimension: 3"; hub od: 0.880" nom.; thread provision: threaded; thread size designator: 5/8-11; recess depth: 1.470" min., 1.530" max.; recess dia.: 0.720" min., 0.780" max.; flange thickness: 0.350" min., 0.410" max.; counterbore depth: 0.125" nom.; counterbore dia.: 0.660" min., 0.720" max.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A521x0