NSN 3010-01-249-6301



Rigid Shaft Coupling - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/3010-01-249-6301 **Spline Minor Diameter:** 0.3960 inches both ends **Spline Major Diameter:** 0.4340 inches both ends **Overall Length:** Between 1.453 inches and 1.463 inches **Spline Quantity:** 26 both ends **Overall Diameter:** Between 0.780 inches and 0.800 inches **End Application:** F-16 aircraft **Bore Shape:** Splined both ends Spline Pressure Angle In Deg: 45.000 both ends Spline Length: 0.828 inches both ends Spline Type: Involute both ends **Features Provided:** Bore counterbore **Body Material:** Steel comp e4340 **Special Features:** Between second end external spline data: 15 teeth; 30.0000 pressure angle; 0.973 in. Major dia; 0.970 in. Minor dia; counterbore diameter: first end, 0.620 in. And 0.640 in.; second end: 0.670 in. And 0.680 in.; counterbore depth: first end, 0.150 in. And 0.170 in.; second end: 0.460 in. And 0.463 in.; pitch diameter: both ends, 0.406 in. **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Cadmium **Style Designator:** Plain sleeve Shelf Life: N/a **Unit Of Measure:**

No

Fiig:

A522c0

Mil-std (military Standard):

Mil-s-5000 spec.

Demilitarization: