NSN 3010-01-291-5913

Flexible Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-01-291-5913

View Online at https://aerobasegroup.com/nsn		
Hole Diameter:		
0.406 inches first end		
Counterbore Diameter:		
4.2500 inches second end		
Counterbore Depth:		
0.7500 inches second end		
Overall Length:		
2.825 inches		
Outside Diameter:		
12.372 inches		
Taper Minor Diameter:		
2.7660 inches through bore		
Keyway Width:		
0.5025 inches through bore		
Keyway Depth:		
0.2990 inches through bore		
Thread Size Designator:		
3/8-16 second end		
Bore Length:		
2.8250 inches through bore		
Bore Shape:		
Tapered both ends		
Design Type:		
Insert		
Keying Facility Quantity:		
1 through bore		
Keying Facility Type:		
Keyway through bore		
Securing Method:		
Unthreaded hole first end		
Threaded Hole Quantity:		
3 second end		
Threaded Hole Location:		
Second end: through body at counterbore		
Unthreaded Hole Quantity:		
8 first end		
Unthreaded Hole Location:		
First end: through flange		
Features Provided:		
Keyway		
Taper Largest Diameter:		

2.8750 inches through bore

NSN 3010-01-291-5913

Flexible Shaft Coupling - Page 2 of 2



Insert	

Rubber

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A522b0