NSN 3010-01-314-9173

Rotary Hydraulic-pneumatic Actuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-01-314-9173 **Body Material:** Steel **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 7.160 inches **Overall Width:** 4.560 inches **End Application:** Used with 2301 electric governor onboard 180 ft wlb coast guard vessels **Shaft Rotation Direction:** Clockwise and counterclockwise **Output Drive Torque Rating:** 43.2 inch-pounds **Mounting Provision Arrangement Style:** Two hole **Pressure Rating:** 400.0 pounds per square inch **Rotation In Deg:** 42.0 **Integral Valve Operation Method:** Electric **Design Characteristics:** Double acting single cylinder **Mounting Facility Diameter:** 0.340 inches **Center To Center Distance Between Mounting Provisions:** 2.250 inches **Special Features:** 0.125-27 nptf (inch) supply oil connection; output shaft 0.375-36 inch serration both ends; shaft driven 0.562-8 special spline; item equipped with 4 pin box mounting receptacle part number ms33682-14s-2p; actuator type eg-3p; vertical mounted Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

Fiig:

A34200