## NSN 3020-00-004-6466

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-004-6466

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.9521 inches and 0.9531 inches
Teeth Quantity:
61
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.9834 inches
Nominallength:
0.312 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.182 inches first end
Face Width:
0.130 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.375 inches first end
Precision Classification:
Quality number 10 or quality number 11
Material:
Aluminum alloy 2024
Material Specification:

Qq-a-225/6, t4 federal specification single material response

## NSN 3020-00-004-6466

Spur Gear - Page 2 of 2



Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.