NSN 3020-00-005-3443

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-005-3443

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.3115 inches and 0.3125 inches
Teeth Quantity:
30
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
0.332 inches
Nominallength:
0.250 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.157 inches first end
Face Width:
0.093 inches
Bore Diameter:
0.078 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.250 inches first end
Precision Classification:
Quality number 10 or quality number 11
Special Features:

Mtg holes spaced 120 degrees apart

NSN 3020-00-005-3443 Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Steel comp 303
Material Specification:
$\ensuremath{Qq}\text{-s-764},$ type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No