NSN 3020-00-005-3492

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-005-3492

Body Style:

Plain, with lightening holes

Attachment Method:

Mounting hole

Pitch Diameter:

Between 1.9995 inches and 2.0000 inches

Teeth Quantity:

96

Bore Style:

Plain both ends

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thready Qty Per Inch (tpi):

40 transversely through hub, first end

Mounting Hole Thread Size:

0.112 inches transversely through hub, first end

Mounting Hole Type And Quantity:

1 threaded transversely through hub, first end

Outside Diameter:

2.039 inches

Nominallength:

0.375 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.250 inches first end

Face Width:

0.125 inches

Bore Diameter:

0.250 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.500 inches first end

Precision Classification:

Quality number 13 or quality number 14

Material:

Steel comp 303

Material Specification:

Mil-s-7720, comp 303s military specification single material response

NSN 3020-00-005-3492

Spur Gear - Page 2 of 2

Surface Treatment:

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.

