NSN 3020-00-005-3524

Spur Gear - Page 1 of 2

Body Style:
Plain, solid
Pitch Diameter:



View Online at https://aerobasegroup.com/nsn/3020-00-005-3524

Between 0.7490 inches and 0.7500 inches					
Teeth Quantity:					
36					
Bore Style:					
Plain both ends					
Backlash Designation:					
Grade c					
Outside Diameter:					
0.792 inches					
Nominallength:					
0.247 inches					
Tooth Form:					
Standard					
Pressure Angle:					
20.0000 degrees					
Distance Between Body Face And Protruding Hub End:					
0.187 inches first end					
Face Width:					
0.063 inches					
Bore Diameter:					
0.187 inches both ends					
Hub Style Designator:					
Plain first end					
Hub Diameter:					
0.375 inches first end					
Precision Classification:					
Quality number 10 or quality number 11					
Material:					
Aluminum alloy 6061					
Material Specification:					
Qq-a-225/8, t6 federal specification single material response					
Surface Treatment:					
Anodize					
Surface Treatment Specification:					
Mil-a-8625, type 2 military specification single treatment response					
Style Designator:					
Protruding hub					
Shelf Life:					
N/a					

NSN 3020-00-005-3524

Spur Gear - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.