
# NSN 3020-00-007-4665

Spur Gear - Page 1 of 2



#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

#### **Pitch Diameter:**

Between 1.2493 inches and 1.2500 inches

#### **Teeth Quantity:**

80

Bore Style:

Plain both ends

- **Outside Diameter:**
- 1.281 inches

#### Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.2810 inches first end

#### Face Width:

0.125 inches

## Bore Diameter:

0.18745 inches both ends

#### Hub Style Designator:

Split first end

#### Hub Diameter:

0.2500 inches first end

#### **Clamping Surface Length:**

0.250 inches first end

#### **Precision Classification:**

Quality number 12

#### **Special Features:**

Hub is also stepped, 0.312 in.Dia, 0.031 in.Lg

### Material:

Aluminum alloy 2024

# Material Specification:

Qq-a-225/6 federal specification single material response

## Surface Treatment:

Anodize hub

# Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response hub

## Style Designator:

Protruding hub



# NSN 3020-00-007-4665

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

# Mil-std (military Standard):

Mil-a-8625 spec.

