NSN 3020-00-007-9428

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-007-9428

| D 1 0/1 |
|---|
| Body Style: |
| Plain, solid |
| Pitch Diameter: |
| Between 0.6868 inches and 0.6875 inches |
| Teeth Quantity: |
| 4 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 0.7182 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.2700 inches first end |
| Face Width: |
| 0.125 inches |
| Bore Diameter: |
| 0.187 inches both ends |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.2500 inches first end |
| Precision Classification: |
| Quality number 12 |
| End Diameter: |
| 0.2500 inches first end |
| First Step Length: |
| 0.0200 inches first end |
| First Step Diameter: |
| 0.5000 inches first end |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-225/6, type 4 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |

Style Designator: Protruding hub

NSN 3020-00-007-9428

Spur Gear - Page 2 of 2



| N/a | |
|---------|----------|
| Unit Of | Measure: |
| | |

Shelf Life:

Demilitarization:

No

Fiig: A27300

Mil-std (military Standard):

Mil-a-8625 spec.