

View Online at <https://aerobasegroup.com/nsn/3020-00-008-3150>

**Counterbore Diameter:**

6.250 inches

**Counterbore Depth:**

0.250 inches

**Outside Diameter:**

Between 10.772 inches and 10.778 inches

**Bolt Circle Diameter:**

7.000 inches

**Thread Size:**

5/16-24

**Bore Diameter:**

Between 3.150 inches and 3.151 inches

**Bore Length:**

1.781 inches

**Pitch Diameter:**

10.822 inches

**Securing Hole Quantity:**

6

**Face Width:**

2.156 inches

**Guide:**

Not included

**Design Form:**

Webbed

**Bore Type:**

Straight

**Counterbore Feature:**

Included

**Counterbore Location:**

Bb end

**Hole Location:**

Through sprocket body

**Keying Facility:**

Not included

**Securing Method:**

Threaded hole

**Lightening Hole:**

Not included

**Securing Location:**

Aa end

**Belt/chain/film Size For Which Designed:**

Positive drive belt

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

68

**Hardness Rating Test Method:**

Not rated

**Bore Bearing:**

Not included

**Tooth Pitch:**

0.500 inches

**Hub End Outside Diameter And Location:**

3.781 inches aa end and 8.125 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.281 inches aa end and 0.094 inches bb end

**Special Features:**

Thd holes equally spaced

**Material:**

Steel, qq-s-631, comp 1010 through 1025

**Material:**

Steel, qq-s-631, comp 1010 through 1025

**Surface Treatment:**

Cadmium

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Cadmium plated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T353-c