NSN 3020-00-010-1530

Spur Gear - Page 1 of 2



n/nsn/3020-00-010-1530 View Online at https://aeroba

View Online at https://aerobasegroup.com/nsn/3020-00-010-18
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
0.9580 inches
Teeth Quantity:
92
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
2 threaded transversely through hub, first end
Outside Diameter:
0.979 inches
Nominallength:
0.362 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.312 inches first end
Face Width:
0.050 inches
Bore Diameter:
0.120 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.300 inches first end
End Diameter:
0.312 inches first end
First Step Length:
0.012 inches first end

First Step Diameter: 0.430 inches first end

NSN 3020-00-010-1530

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-7720 spec.



Material:
Steel comp 302
Material Specification:
Mil-s-7720 military specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300