## NSN 3020-00-010-1530

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-010-1530

**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.9580 inches **Teeth Quantity:** 92 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end Mounting Hole Thread Size: 0.086 inches transversely through hub, first end Mounting Hole Type And Quantity: 2 threaded transversely through hub, first end **Outside Diameter:** 0.979 inches Nominallength: 0.362 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.312 inches first end Face Width: 0.050 inches **Bore Diameter:** 0.120 inches both ends Hub Style Designator: 1 step first end End Length: 0.300 inches first end End Diameter: 0.312 inches first end First Step Length: 0.012 inches first end **First Step Diameter:** 0.430 inches first end

## NSN 3020-00-010-1530

Spur Gear - Page 2 of 2



Material:

Steel comp 302

Material Specification:

Mil-s-7720 military specification single material response

Surface Treatment:

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

## Mil-std (military Standard):

Mil-s-7720 spec.