NSN 3020-00-016-4520

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-016-4520

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| Between 1.7490 inches and 1.7500 inches |
| Teeth Quantity: |
| 84 |
| Mounting Hole Type And Quantity: |
| 1 plain axially through body, first end |
| Outside Diameter: |
| 1.791 inches |
| Nominallength: |
| 0.350 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.285 inches first end |
| Face Width: |
| 0.065 inches |
| Bore Diameter: |
| 0.188 inches both ends |
| Hub Diameter: |
| 0.400 inches first end |
| Precision Classification: |
| Quality number 10 or quality number 11 |
| Bolt Hole Circle Diameter: |
| 0.250 inches axially through body, first end |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-225/8, t6 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 3020-00-016-4520

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300