## NSN 3020-00-017-3153

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-017-3153 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.8115 inches and 0.8125 inches **Teeth Quantity:** 39 **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.853 inches Nominallength: 0.295 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.202 inches first end **Face Width:** 0.093 inches **Bore Diameter:** 0.187 inches both ends **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Aluminum alloy 6061 **Material Specification:** Qq-a-225/8, t6 federal specification single material response **Surface Treatment:** Anodize **Style Designator:** 

Protruding hub Shelf Life: N/a

## **NSN 3020-00-017-3153** Spur Gear - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A27300