
# NSN 3020-00-019-2746

Spur Gear - Page 1 of 2



#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

# **Pitch Diameter:**

Between 2.2490 inches and 2.2500 inches

## **Teeth Quantity:**

108

#### Bore Style:

Plain both ends

### **Outside Diameter:**

2.2910 inches

#### Nominallength:

0.405 inches

#### **Tooth Form:**

Standard

# Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.313 inches first end

## Face Width:

0.093 inches

## Bore Diameter:

0.241 inches both ends

#### Hub Style Designator:

Split first end

#### Hub Diameter:

0.313 inches first end

### Clamping Surface Length:

0.270 inches first end

### **Precision Classification:**

Quality number 10 or quality number 11

#### Material:

Steel comp 416

### **Material Specification:**

Qq-s-764, type 416 cond a federal specification single material response

# Surface Treatment:

Passivate

# Style Designator:

Protruding hub

# Shelf Life:

N/a



# NSN 3020-00-019-2746

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

