## NSN 3020-00-019-3174

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-019-3174

Mounting hole Pitch Diameter: 2.0000 inches Teeth Quantity: 128 Bore Style: Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end
2.0000 inches Teeth Quantity: 128 Bore Style: Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end
Teeth Quantity: 128 Bore Style: Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end
128 Bore Style: Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end
Bore Style: Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end
Plain both ends <b>Mounting Hole Thread Series Designator:</b> Unc transversely through hub, first end
Mounting Hole Thread Series Designator: Unc transversely through hub, first end
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Thread Size:
0.086 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
2.0312 inches
Nominallength:
0.406 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.312 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.750 inches first end
Material:
Copper alloy 360 body
Material Specification:
Qq-b-626, alloy 360, 1/2 h federal specification single material response body
Style Designator:
Protruding hub
Shelf Life:
N/a

## NSN 3020-00-019-3174

Spur Antibacklash Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

