## NSN 3020-00-020-3954



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-020-3954 **Attachment Method:** Mounting hole Pitch Diameter: 1.2500 inches **Teeth Quantity:** 80 **Bore Style:** Plain both ends **Backlash Designation:** Grade a **Mounting Hole Thread Series Designator:** Unc axially through hub, second end **Mounting Hole Thread Size:** 0.086 inches axially through hub, second end **Mounting Hole Type And Quantity:** 1 threaded axially through hub, second end **Outside Diameter:** 1.276 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.032 inches second end **Face Width:** 0.062 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.257 inches second end **End Length:** 0.138 inches first end **Precision Classification:** Quality number 10 or quality number 11 **End Diameter:** 0.245 inches first end First Step Length: 0.031 inches first end

First Step Diameter: 0.625 inches first end

## NSN 3020-00-020-3954

**Fiig:** A27300

Spur Antibacklash Gear - Page 2 of 2



Material:
Steel comp 303 hub
Material Specification:
Qq-s-766, cond a federal specification single material response hub
Surface Treatment:
Passivate
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No