## NSN 3020-00-021-3125

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-021-3125

| Body Style:   |  |  |
|---|--|--|
| Plain, solid  |  |  |
| Attachment Method:  |  |  |
| Mounting hole   |  |  |
| Pitch Diameter:   |  |  |
| Between 2.6657 inches and 2.6667 inches                       |  |  |
| Teeth Quantity:   |  |  |
| 128   |  |  |
| Bore Style:   |  |  |
| Plain both ends   |  |  |
| Mounting Hole Type And Quantity:                              |  |  |
| 2 plain transversely through hub, first end                   |  |  |
| Outside Diameter:   |  |  |
| 2.707 inches  |  |  |
| Nominallength:  |  |  |
| 0.435 inches  |  |  |
| Tooth Form:   |  |  |
| Standard  |  |  |
| Pressure Angle:   |  |  |
| 20.0000 degrees   |  |  |
| Distance Between Body Face And Protruding Hub End:            |  |  |
| 0.340 inches first end  |  |  |
| Face Width:   |  |  |
| 0.095 inches  |  |  |
| Bore Diameter:  |  |  |
| 0.241 inches both ends  |  |  |
| Hub Style Designator:   |  |  |
| Pinned first end  |  |  |
| Hub Diameter:   |  |  |
| 0.620 inches first end  |  |  |
| Precision Classification:                                     |  |  |
| Quality number 10 or quality number 11                        |  |  |
| Mounting Hole Diameter:                                       |  |  |
| 0.112 inches axially through hub, first end                   |  |  |
| Bolt Hole Circle Diameter:                                    |  |  |
| 0.438 inches axially through hub, first end                   |  |  |
| Material:   |  |  |
| Aluminum alloy 6061   |  |  |
| Material Specification:                                       |  |  |
| Qq-a-225/8, t6 federal specification single material response |  |  |
| Style Designator:   |  |  |
| Ductionalise a book   |  |  |

Protruding hub

## NSN 3020-00-021-3125

Spur Gear - Page 2 of 2



|  | Life: |
|--|-------|
|  |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300