
NSN 3020-00-021-3155

Spur Gear - Page 1 of 2

Body Style:

22





Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** 0.4580 inches **Teeth Quantity: Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end Mounting Hole Thread Size: 0.112 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.500 inches Nominallength: 0.325 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.200 inches first end Face Width: 0.125 inches **Bore Diameter:** 0.187 inches both ends Hub Style Designator: Plain first end **Hub Diameter:** 0.375 inches first end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response Surface Treatment: Anodize

NSN 3020-00-021-3155

Spur Gear - Page 2 of 2

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

