## NSN 3020-00-025-7566

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-025-7566

| Pody Style:   |
|---|
| Body Style: Webbed, offset, solid                                       |
| Pitch Diameter:   |
| 3.000 inches  |
| Teeth Quantity:   |
| 144   |
| Bore Style:   |
| Plain both ends   |
| Outside Diameter:   |
| 3.0401 inches   |
| Tooth Form:   |
| Standard  |
| Pressure Angle:   |
| 20.0000 degrees   |
| Distance Between Body Face And Protruding Hub End:                      |
| 0.5650 inches first end   |
| Distance Between Body Face And Recessed Hub End:                        |
| 0.1310 inches second end  |
| Face Width:   |
| 0.3750 inches   |
| Bore Diameter:  |
| 0.4725 inches both ends   |
| Hub Style Designator:   |
| Plain both ends   |
| Hub Diameter:   |
| 1.000 inches both ends  |
| Special Features:   |
| 2 positioning holes 0.115 in. Dia, 90.0 degrees apart on protruding hub |
| Material:   |
| Aluminum alloy 2024   |
| Material Specification:   |
| Qq-a-250/4, t3 federal specification single material response           |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mil-a-8625, type 2 military specification single treatment response     |
| Style Designator:   |
| One protruding hub, one recessed hub                                    |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 3020-00-025-7566

Spur Gear - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.