NSN 3020-00-027-4719

Spur Gear - Page 1 of 2





Body Style:

Plain, solid

Attachment Method:

Mounting hole

Pitch Diameter:

Between 0.8115 inches and 0.8125 inches

Teeth Quantity:

52

Bore Style:

Plain both ends

Mounting Hole Type And Quantity:

1 plain axially through body, first end

Outside Diameter:

0.843 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

0.280 inches first end

Face Width:

0.095 inches

Bore Diameter:

0.188 inches both ends

Hub Style Designator:

Plain first end

Hub Diameter:

0.400 inches first end

Precision Classification:

Quality number 10 or quality number 11

Mounting Hole Diameter:

0.0435 inches axially through body, first end

Bolt Hole Circle Diameter:

0.5000 inches axially through body, first end

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8, t6 federal specification single material response

Surface Treatment:

Anodize

Style Designator:

Protruding hub

NSN 3020-00-027-4719

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

