## NSN 3020-00-033-2110

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-033-2110

S	pline	Ma	ior	Dia	mete	r:
_	• • • • • •		,			

Between 2.248 inches and 2.250 inches

**Outside Diameter:** 

Between 6.815 inches and 6.831 inches

**Overall Length:** 

Between 1.872 inches and 1.878 inches

**Spline Quantity:** 

10

**Spline Minor Diameter:** 

Between 1.933 inches and 1.935 inches

Pitch Diameter:

Between 5.952 inches and 5.968 inches

**Face Width:** 

Between 1.398 inches and 1.407 inches

**Design Form:** 

Webbed

**Bore Type:** 

Straight spline

Spline Length:

Between 1.872 inches and 1.878 inches

**Counterbore Feature:** 

Not included

**Lightening Hole:** 

Included

**Protruding Hub Characteristic:** 

Plain

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

**Teeth Row Quantity:** 

3

**Center To Center Distance Between Teeth Rows:** 

Between 0.558 inches and 0.568 inches

**Teeth Quantity Per Row:** 

11

**Asa Standard Chain Number:** 

E-40

**Hardness Rating Test Method:** 

Not rated

**Bore Bearing:** 

Not included

## **NSN 3020-00-033-2110** Sprocket Wheel - Page 2 of 2



Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
3.000 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.232 inches aa end and 0.240 inches aa end
Material:
Iron, cast
Material:
Iron cast
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c