

View Online at <https://aerobasegroup.com/nsn/3020-00-034-2193>

Groove Depth:

0.812 inches

Groove Width:

Between 0.500 inches and 0.875 inches

Outside Diameter:

4.750 inches

Overall Length:

1.875 inches

Keyway Width:

0.188 inches

Thread Size:

0.312-18

Bore Diameter:

0.625 inches

Bore Length:

1.875 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.406 inches

V Groove Angle In Deg:

36.0

Pitch Diameter:

Between 3.300 inches and 4.700 inches

Securing Hole Quantity:

1

Furnished Items And Quantity:

Setscrew, one each

Material And Location:

Iron, cast

Face Width:

Between 0.688 inches and 1.062 inches

Design Form:

Plain

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

Centered 0.188 in.From face of hub, top of keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

3I-4I-5I-a-b

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Bb end

Hub End Outside Diameter And Location:

2.000 inches aa end and 1.562 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.438 inches aa end and 0.312 inches bb end

Quantity:

1

Surface Treatment:

Paint

Style Designator:

Plain

Surface Treatment:

Painted

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a