NSN 3020-00-038-1598



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-038-1598 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.3125 inches **Teeth Quantity:** 20 **Bore Style:** W/ keyway both ends **Hardness Rating:** 52.0 rockwell c and 55.0 rockwell c **Mounting Hole Type And Quantity:** 1 plain axially through body, first end **Outside Diameter:** 0.3380 inches Nominallength: 0.409 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.3590 inches first end **Face Width:** 0.050 inches **Keyway Width:** 0.031 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.0625 inches both ends **Hub Style Designator:** 1 groove first end **End Diameter:** 0.186 inches first end **First Groove Width:** 0.175 inches first end **First Groove Diameter:** 0.1750 inches first end **Distance From End To First Groove:**

0.0470 inches first end

Mounting Hole Diameter:

0.046 inches transversely through hub, first end

NSN 3020-00-038-1598 Spur Gear - Page 2 of 2

Fiig: A27300



Material:
Steel comp 440c
Material Specification:
Qq-s-763 class440c federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No