

View Online at <https://aerobasegroup.com/nsn/3020-00-038-4335>

Groove Depth:

0.750 inches and 0.750 inches and 0.625 inches

Groove Width:

Between 0.873 inches and 0.877 inches

Overall Length:

2.250 inches

Bolt Circle Diameter:

3.750 inches

Keyway Width:

Between 0.313 inches and 0.314 inches

Thread Size:

7/16-14

Bore Diameter:

Between 1.375 inches and 1.376 inches

Bore Length:

1.609 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.8362 inches

Drilled Hole Diameter:

0.625 inches

Groove Radius:

0.031 inches

Securing Hole Quantity:

3

Face Type:

Step groove

Material And Location:

Iron, 41-002-00, cummins engine co

Face Width:

3.250 inches

Design Form:

Plain

Bore Type:

Straight

Groove Quantity:

3

Counterbore Feature:

Not included

Step Outside Diameter:

9.500 inches and 7.250 inches

Hole Location:

One hole on top of keyway, one hole 180 degrees from keyway, one hole 90 degrees from keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Drilled hole or threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

U

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Bore Bearing:

Not included

Hub End Outside Diameter And Location:

2.128 inches aa end and 2.123 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.047 inches aa end

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-b