## NSN 3020-00-038-7139

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-038-7139

view Online at https://aerobasegroup.com/nsn/3020-00-038-7139
Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 2.0927 inches and 2.0937 inches
Teeth Quantity:
134
Bore Style:
W/counterbore counterbore, first end
Mounting Hole Type And Quantity:
2 plain axially through body, first end
Outside Diameter:
2.124 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Face Width:
0.125 inches
Bore Diameter:
0.625 inches counterbore, first end
Counterbore Depth:
0.063 inches counterbore, first end
Counterbore Diameter:
1.313 inches counterbore, first end
Precision Classification:
Quality number 10 or quality number 11
Mounting Hole Diameter:
0.124 inches axially through body, first end
Bolt Hole Circle Diameter:
0.937 inches axially through body, first end
Special Features:
Mtg holes spaced 180 degrees apart
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response

## NSN 3020-00-038-7139

Spur Gear - Page 2 of 2



Style Designator:
Hubless
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization:

Mil-std (military Standard):

Mil-f-14072 spec.