## NSN 3020-00-038-7177

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-038-7177 **Attachment Method:** Mounting hole **Pitch Diameter:** Between 1.1451 inches and 1.1458 inches **Teeth Quantity:** 55 **Bore Style:** Plain both ends **Backlash Designation:** Grade e **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 1.186 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.281 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.090 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end **Precision Classification:** Quality number 12 **Special Features:** Mtg holes spaced 90 degrees apart, one unthd hole 0.032 in. Diameter through body Material: Steel comp 303 **Material Specification:** 

Qq-s-764, type 303, cond a federal specification single material response

**Style Designator:** Protruding hub

## NSN 3020-00-038-7177

Spur Antibacklash Gear - Page 2 of 2



Shelf	LIIE.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300