## NSN 3020-00-039-8500



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-039-8500 **Body Style:** Webbed, offset, solid **Spline Quantity:** 14 both ends Pitch Diameter: 4.3330 inches **Teeth Quantity:** 52 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 0.7000 inches both ends Hardness Rating: 34.0 rockwell c and 38.0 rockwell c **Outside Diameter:** 4.466 inches Nominallength: 3.312 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 1.312 inches second end **Face Width:** 0.312 inches **Bore Diameter:** 0.706 inches both ends **Hub Style Designator:** 2 steps first end **End Length:** 0.432 inches first end **End Diameter:** 1.250 inches first end First Step Length: 0.812 inches first end First Step Diameter: 1.379 inches first end

1.379 inches first end
Second Step Length:
0.081 inches first end
Second Step Diameter:

1.656 inches first end

## **NSN 3020-00-039-8500** Spur Gear - Page 2 of 2



Third Step Length:
0.438 inches first end
Third Step Diameter:
4.062 inches first end
Special Features:
Pin, tacom p/n 7963254, welded into hole in gear face1.782 in.From gear center.Hole diameter 0.1875 in.
Material:
Steel
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli
Fiig:
A27300