

View Online at <https://aerobasegroup.com/nsn/3020-00-040-2169>

**Outside Diameter:**

2.4375 inches

**Overall Length:**

1.3125 inches

**Keyway Width:**

0.250 inches

**Thread Size:**

1/4 in.-20

**Bore Diameter:**

Between 1.125 inches and 1.126 inches

**Bore Length:**

1.3125 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.683 inches

**Pitch Diameter:**

2.415 inches

**Securing Hole Quantity:**

1

**Furnished Items And Quantity:**

One 1/4 in. -20 by 3/16 in. Lg setscrew

**Face Width:**

0.240 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Metallic Hardness Rating And Location:**

58.0 rockwell c body

**Counterbore Feature:**

Not included

**Hole Location:**

Located on top of keyway

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Stepped

**Groove/step Location:**

Aa end

**Securing Location:**

Aa end

**Belt/chain/film Size For Which Designed:**

Roller chain

**Roller Chain Pitch Type For Which Designed:**

Single pitch

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

12

**Asa Standard Chain Number:**

50

**Hardness Rating Test Method:**

Rockwell

**Teeth Hardness Rating:**

50.0 rockwell c

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

0.625 inches

**Distance From Outside Flange/rim To Hub End And Location:**

1.0625 inches both ends and 1.0625 inches both ends

**Special Features:**

First step face largest diameter 1.6875 in., first step length 0.500 in., second step length 0.5625 in.

**Material:**

Steel

**Material:**

Steel

**Quantity:**

1

**Style Designator:**

Plain

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c