

View Online at <https://aerobasegroup.com/nsn/3020-00-040-2169>

Outside Diameter:

2.4375 inches

Overall Length:

1.3125 inches

Keyway Width:

0.250 inches

Thread Size:

1/4 in.-20

Bore Diameter:

Between 1.125 inches and 1.126 inches

Bore Length:

1.3125 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.683 inches

Pitch Diameter:

2.415 inches

Securing Hole Quantity:

1

Furnished Items And Quantity:

One 1/4 in. -20 by 3/16 in. Lg setscrew

Face Width:

0.240 inches

Design Form:

Plain

Bore Type:

Straight

Metallic Hardness Rating And Location:

58.0 rockwell c body

Counterbore Feature:

Not included

Hole Location:

Located on top of keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Stepped

Groove/step Location:

Aa end

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

12

Asa Standard Chain Number:

50

Hardness Rating Test Method:

Rockwell

Teeth Hardness Rating:

50.0 rockwell c

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

0.625 inches

Distance From Outside Flange/rim To Hub End And Location:

1.0625 inches both ends and 1.0625 inches both ends

Special Features:

First step face largest diameter 1.6875 in., first step length 0.500 in., second step length 0.5625 in.

Material:

Steel

Material:

Steel

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-c