## NSN 3020-00-041-2091

Spur Gear - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3020-00-041-2091



**Body Style:** Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** Between 0.7888 inches and 0.7916 inches **Teeth Quantity:** 38 **Bore Style:** Plain both ends Mounting Hole Thread Series Designator: Unc transversely through hub, first end Hardness Rating: 262.0 brinell standard Mounting Hole Thread Size: 0.138 inches transversely through hub, first end Mounting Hole Type And Quantity: 1 threaded transversely through hub, first end **Outside Diameter:** 0.834 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.441 inches first end Face Width: 0.060 inches **Bore Diameter:** 0.251 inches both ends Hub Style Designator: 1 step first end End Length: 0.420 inches first end End Diameter: 0.435 inches first end First Step Length: 0.023 inches first end **First Step Diameter:** 0.625 inches first end **Special Features:** 

Groove located on 1st end hub 0.020 in. W, 0.405 in. Dia

## NSN 3020-00-041-2091

Spur Gear - Page 2 of 2



Material:

Steel comp 303

## Material Specification:

Qq-s-763, class303 federal specification single material response

Surface Treatment:

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300