NSN 3020-00-041-2535

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-041-2535 **Pitch Diameter:** Between 1.6657 inches and 1.6667 inches **Teeth Quantity:** 120 **Bore Style:** Plain both ends **Outside Diameter:** 1.693 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.221 inches first end **Face Width:** 0.104 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.312 inches first end **Clamping Surface Length:** 0.190 inches first end **Precision Classification:** Quality number 10 or quality number 11 Material: Steel comp 303 hub **Material Specification:** Qq-s-764, type 303, cond 4 federal specification single material response hub **Surface Treatment:** Passivate hub **Surface Treatment Specification:** Mil-a-8625 type 1 military specification 1st treatment response teeth **Style Designator:** Protruding hub Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 3020-00-041-2535

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.