NSN 3020-00-042-3912

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-042-3912

Attachment Method: Mounting hole Pitch Diameter: 1.5000 inches **Teeth Quantity:** 144 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.519 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.200 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.375 inches first end **Precision Classification:** Quality number 12 Material: Aluminum alloy **Material Specification:**

52s-h32, aeroflex laboratories mfr ref single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Protruding hub

NSN 3020-00-042-3912

Spur Antibacklash Gear - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| | |
| Fiig: | |

Mil-std (military Standard):

Mil-a-8625 spec.

Shelf Life: