
# NSN 3020-00-042-6596

Spur Gear - Page 1 of 2





Body Style:

Plain, solid

#### **Attachment Method:**

Clamp

### **Pitch Diameter:**

Between 1.8740 inches and 1.8750 inches

# **Teeth Quantity:**

120

Bore Style:

Plain both ends

**Outside Diameter:** 

1.905 inches

#### Tooth Form:

Standard

### Pressure Angle:

20.0000 degrees

# Distance Between Body Face And Protruding Hub End:

0.221 inches first end

#### Face Width:

0.104 inches

# Bore Diameter:

0.187 inches both ends

# Hub Style Designator:

Split first end

# Hub Diameter:

0.250 inches first end

# **Clamping Surface Length:**

0.286 inches first end

# Material:

Aluminum alloy 2024

# **Material Specification:**

Qq-a-225/6, t4 federal specification single material response

#### Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

# Style Designator:

Protruding hub

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 3020-00-042-6596

Spur Gear - Page 2 of 2

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.

