NSN 3020-00-043-2219



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-043-2219 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.2083 inches **Teeth Quantity:** 20 **Bore Style:** Plain both ends **Backlash Designation:** Grade e **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.229 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.281 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.094 inches both ends **Hub Style Designator:** 1 step first end

End Length:
0.156 inches first end
Precision Classification:
Quality number 13
End Diameter:
0.312 inches first end
First Step Length:
0.125 inches first end
First Step Diameter:
0.156 inches first end

NSN 3020-00-043-2219

Spur Gear - Page 2 of 2

Mil-s-7720 spec.



Material:
Steel comp 303
Material Specification:
Mil-s-7720 military specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):