## NSN 3020-00-049-5381



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-049-5381 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7187 inches **Teeth Quantity:** 46 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 40 transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.750 inches Nominallength: 0.250 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.188 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.187 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.312 inches first end Material: Steel comp 303 **Material Specification:** 

Qq-s-763, class 303, cond a federal specification single material response

**Surface Treatment:** 

**Passivate** 

## NSN 3020-00-049-5381

Spur Gear - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Mil-f-14072, finish e300 military specification single treatment response

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.