## NSN 3020-00-049-8548

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-00-049-8548

Webbed, offset, solid
Attachment Method:
Mounting hole
Pitch Diameter:
11.6250 inches
Teeth Quantity:
186
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through hub, first end and unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
24 axially through hub, first end
Hardness Rating:
29.0 rockwell c and 32.0 rockwell c
Mounting Hole Thread Size:
0.190 inches axially through body, first end and 0.250 inches axially through body, first end
Mounting Hole Type And Quantity:
8 threaded axially through hub, first end and 8 threaded axially through hub, first end
Outside Diameter:
11.750 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Recessed Hub End:
0.1875 inches first end
Face Width:
0.500 inches
Bore Diameter:
3.4375 inches first end
Hub Style Designator:
Plain first end
Hub Diameter:
6.000 inches first end
Special Features:
Mounting facility screw thd q type 20 per in.
Material:
Steel comp 4140 or steel body
Material Specification:
66 federal standard single material response and aisi/sae 4140 assn standard single material response

## NSN 3020-00-049-8548

Spur Gear - Page 2 of 2



_	•	-	_		
<b>C</b> :	ırta	2	ros	at m	ent:

Zinc side plate

Style Designator:

Recessed hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300