NSN 3020-00-049-9291

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-049-9291 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.2500 inches **Teeth Quantity:** 25 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 24 transversely through hub, first end **Mounting Hole Thread Size:** 0.190 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.345 inches Nominallength: 0.750 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.380 inches first end **Face Width:** 0.370 inches **Bore Diameter:** 0.499 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 1.114 inches first end Material: Steel comp 1211 or steel comp 1213 or steel comp 1117 or steel comp 1118 or steel comp 1119 **Material Specification:** 66, aisi b1111 federal standard 1st material response or 66, aisi b1113 federal standard 2nd material response or 66, aisi/sae 1117 federal standard 3rd material response or 66, aisi/sae 1118 federal standard 4th material response or 66 aisi/sae 1119 federal standard 5th

Phosphate

material response

Surface Treatment:

NSN 3020-00-049-9291

Spur Gear - Page 2 of 2



~ .			
Stvi	e ve	sıan	ator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300