NSN 3020-00-050-2029



Spur Antibacklash Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-050-2029 **Attachment Method:** Mounting hole Pitch Diameter: 0.3594 inches **Teeth Quantity:** 23 **Bore Style:** Plain both ends **Backlash Designation:** Grade b **Mounting Hole Thread Series Designator:** Unf transversely through hub, first end **Mounting Hole Thread Size:** 0.073 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.3906 inches Nominallength: 0.281 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.011 inches second end **Face Width:** 0.093 inches **Bore Diameter:** 0.094 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.243 inches first end Material: Steel comp 303 **Material Specification:** Qq-s-764, type 303, cond a federal specification single material response **Surface Treatment: Passivate**

Style Designator: Peripheral face, hubless

NSN 3020-00-050-2029

Spur Antibacklash Gear - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300